

# Andisil® EM 7060



## TYPICAL PROPERTIES\*

APPEARANCE	Milky white liquid
SILICONE CONTENT	60 %
SPECIFIC GRAVITY	0.997

\* These values are not intended to be used as specifications but only as suggested characteristics

## DESCRIPTION

Andisil® EM 7060 is a non-ionic, 60% emulsion of silanol terminated polydimethylsiloxane. It is easily diluted by adding water with mild agitation. It can be used as a release agent in the following applications.

- Shell Core
- Plastics
- Asphalt
- Metals

## STORAGE & SHELF LIFE

The shelf life, when the container is stored unopened and under proper conditions (in temperatures above 35° - do not allow to freeze), is expected to be a minimum of twelve months.

## PACKAGING & HANDLING

The Andisil® EM 7060 Silicone Emulsion is supplied in 440 pound net weight plastic drums, other packaging options are available upon request. Prior to use, it is recommended that the product be gently agitated for ten to twenty minutes prior to using to insure a uniform material.

For additional information on the product, please contact your Sales Representative.



We believe that the information shown in this Product Bulletin to be an accurate description of the typical characteristics and/or uses of the product. Any suggestions of uses are not to be taken as an inducement to infringe any particular domestic or foreign patent. We recommend that the product be thoroughly tested for a specific application to determine the performance, efficacy and its safe handling and use.

AB Specialty Silicones | 3725 Hawthorn Court | Waukegan, IL 60087

☎ 908.273.8015 | TOLL FREE 800.678.3024 | FAX 224.232.1999 | ✉ info@andisil.com

Rev 3-SO-6/19